

1189 Low Pressure Bellows Gauge

FEATURES

- Inches of water ranges
- Available with diaphragm seals
- Bellows-actuated mechanism
- Easy adjustable micrometer pointer
- Solid front safety case with pressure relief back
- Brass, 316 Stainless steel or Monel® wetted parts

TYPICAL USES

- Oil & gas
- Chemical and petrochemical plants
- Water and wastewater pressure control
- Equipment skids
- Process and industrial applications



1189
4½", 6" dial size

SPECIFICATIONS

Accuracy:	+/-2%-1%-2% (ASME Grade A)
Dial Size:	4½", 6"
Process Connection Location:	Lower
Process Connection Size:	¼ NPT Male, ½ NPT Male
Case Style:	Solid Front (dry only)
Movement:	416 Stainless steel
Window Material:	Glass (STD.), Shatter Proof Glass (OPT.)
Dial:	White Aluminum with Black Markings
Pointer:	Micrometer Adjustable
Mounting:	Stem, Surface

WETTED COMPONENTS

Bellows	Process Connection	Joints
Brass	Brass	Soldered: Brass
316 SS	316 SS	Welded: 316 SS
Monel®	Monel®	Monel®

NON-WETTED COMPONENTS

Case	Ring	Back Cover
Aluminum	Polycarbonate	Polypropylene

KEY BENEFITS

- Highly sensitive system providing a safe means for measuring process media
- Ideal product solution for many installations
- Rugged design

MIN/MAX TEMPERATURE LIMITS

Version	Ambient	Process	Storage
Dry	-20°F to 150°F (-29°C to 66°C)	-20°F to 150°F (-29°C to 66°C)	-40°F to 150°F (-40°C to 66°C)

Data Sheet

1189 Low Pressure Bellows Gauge

ORDERING CODE	Example:	451189	S	S	02	L	XC4	10IW
Dial Size/Model Code								
451189 - 4½" aluminum case, solid front		451189						
601189 - 6" aluminum case, solid front								
System (tube and process connection)								
A - Brass bellows, brass process connection								
S - 316 Stainless steel bellows, stainless steel process connection			S					
P - K-Monel® 500 bellows, Monel® 400 process connection								
Case Design								
S - Solid front, Dry				S				
Process Connection Sizes								
02 - ¼ NPT Male					02			
04 - ½ NPT Male								
Process Connection Location								
L - Lower						L		
Options (If choosing an option(s) must include an "X")								
C4 - Individual calibration chart (in accordance with ASME B40.100:2013. Accuracy traceable to N.I.S.T)							X_	C4
D3 - DuraVis™ Retroreflective Dial (4½" case only)								
6B - Cleaned for gaseous oxygen service								
F8 - Gauge, flexible line assembly and diaphragm seal								
PD - Acrylic window								
SG - Safety glass								
NG - Non-glare glass								
DA - Marking on dial								
NH - Stainless steel tag wired to case								
NN - Paper tag bonded to case								
56 - Flush mounting ring								
Range (coding examples only, see range table on page 3 for all standard ranges)								
Single Scales								
10IW - 10" H ₂ O								10IW

Data Sheet

1189 Low Pressure Bellows Gauge

STANDARD PRESSURE RANGE							
	in. H ₂ O	mmHg	in. Hg	mmH ₂ O	psi	mbar	kPa
Vacuum	N10IW	N18MM	-	-	-	-	-
	N15IW	N28MM	-	-	-	-	-
	N20IW	N37MM	-	-	-	-	-
	N30IW	N56MM	-	-	-	-	-
	N40IW	N75MM	-	-	-	-	-
	N60IW	N110MM	-	-	-	-	-
	N80IW	N150MM	-	-	-	-	-
	N100IW	N180MM	-	-	-	-	-
	N150IW	N270MM	-	-	-	-	-
	-	-	N10IM	-	-	-	-
-	-	N15IM	-	-	-	-	-
-	-	N20IM	-	-	-	-	-
-	-	-	N125/125MW	-	N12.5/12.5MB	N1.25/1.25KP	-
N5/5IW	-	-	-	-	-	-	-
-	-	-	N200/200MW	-	N20/20MB	N2/2KP	-
N10/10IW	-	-	-	-	-	-	-
-	-	-	N300/300MW	-	N30/30MB	N3/3KP	-
-	-	-	N500/500MW	-	N50/50MB	N5/5KP	-
Compound	N30/10IW	-	-	-	-	-	-
	N20/20IW	-	-	-	-	-	-
	N10/30IW	-	-	-	-	-	-
	N30/30IW	-	-	-	-	-	-
	N40/20IW	-	-	N800/800MW	-	N80/80MB	N8/8KP
	-	-	N1250/1250MW	-	N125/125MB	N12.5/12.5KP	-
	N70/30IW	-	-	-	-	-	-
	-	-	N2000/2000MW	-	N200/200MB	N20/20KP	-
	-	-	N3000/3000MW	-	N300/300MB	N30/30KP	-
	5IW	-	-	-	-	-	-
10IW	-	-	250MW	-	25MB	2.5KP	
15IW	-	-	-	-	-	-	
-	-	-	400MW	-	-	-	
-	-	-	-	-	40MB	4KP	
20IW	-	-	-	-	-	-	
-	-	-	600MW	-	-	-	
-	-	-	-	-	60MB	6KP	
30IW	-	-	-	-	-	-	
-	-	-	1000MW	-	-	-	
40IW	-	-	-	-	100MB	10KP	
-	-	-	-	-	-	-	
60IW	-	-	-	-	-	-	
-	-	-	1600MW	-	-	-	
-	-	-	-	-	160MB	16KP	
80IW	-	-	-	-	-	-	
-	-	-	2500MW	-	-	-	
100IW	-	-	-	-	250MB	25KP	
-	-	-	-	5#	-	-	
150IW	-	-	-	-	-	-	
-	-	-	4000MW	-	-	-	
-	-	-	-	-	400MB	40KP	
-	-	-	-	8#	-	-	
-	-	-	6000MW	-	-	-	
-	-	-	-	-	600MB	60KP	
-	-	-	-	10#	-	-	

Data Sheet

1189 Low Pressure Bellows Gauge

DIMENSIONS in [] are millimeters

For reference only, consult Ashcroft for specific dimensional drawings

Dial Size Inches	A	B	C	D	E	G	I	J	L	Weight (lbs)
4 1/2"	5 3/16 [148]	3 13/32 [87]	4 7/8 [124]	1 11/16 [43]	5 3/8 [137]	1 1/2 [38]	5/8 [16]	1 1/8 [29]	7/32 [5,5]	2.5 1.1 kg
6"	7 7/16 [192]	3 1/2 [89]	6 5/8 [162]	1 11/16 [43]	7 [178]	1 1/2 [38]	5/8 [16]	1 1/8 [29]	9/32 [7,5]	3.13 1.4 kg

